



SHERLINER® SOLVENT-BASED STRIPING PAINT

AEROSOL PAINT

Product Numbers: 1600006, 1600014, 1600022, 1600030, 1600329

PRODUCT DESCRIPTION	APPLICATION CONT.	CAUTIONS
<p>SherLiner® Solvent-Based Striping Paints make striping any surface easy. These solvent-based paints produce bright, crisp lines. Perfect for short-term striping projects such: warehouse aisles, parking lots, construction sites, school grounds, road surfaces, nurseries, apartment complexes, fairgrounds.</p> <p>Product Features:</p> <ul style="list-style-type: none"> - Fast drying - High solids - Non-clog spray - One-coat coverage - Long-lasting durability - VOC/MIR compliant 	<p>an 18 gauge, all steel construction and is equipped with 12-can storage. Creates professional striping results in widths of 2" to 4" on any ground surface. For storage or re-use, it is best to clear the spray tip by holding the can in an upright position pointed away from you, and push the tip to one side for a few seconds to clear paint out.</p>	<p>CONTAINS ALIPHATIC HYDROCARBONS, TOLUENE, KETONES AND XYLENE. DANGER! EXTREMELY FLAMMABLE. Keep away from sparks, heat or open flames. Vapors will accumulate readily and may ignite explosively. Keep area ventilated during use and until all vapors are gone. DO NOT SMOKE - Extinguish all flames, pilot lights and heaters - Turn off stoves, electric tools and appliances, and any other sources of ignition. CONTENTS UNDER PRESSURE. Avoid prolonged exposure to sunlight or heat from radiators, stoves, hot water and other heat sources that may cause bursting. Do not puncture, incinerate, burn or store above 120°F. Keep upright in a cool, dry place. Do not discard empty can in trash compactor. VAPOR HARMFUL. Use with adequate ventilation. Avoid continuous breathing of vapor and spray mist. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection (NIOSH approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. FIRST AID: In case of eye contact, flush thoroughly with large amounts of water for 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water. In case of respiratory difficulty, provide fresh air and call physician. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.</p>
SURFACE PREPARATION	CHARACTERISTICS	
<p>WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Hotline at 1-800-424-LEAD or log onto www.epa.gov/lead. Surfaces to be striped should be free from any contaminants (dirt, debris, etc.). For pavement applications, sweep area to be striped before you begin.</p>	<p>Color: 5 Colors White, Yellow, Red, Blue, Black</p> <p>Coverage: 400 to 600 sq. ft.</p> <p>Drying Time, @ 77°F, 50% RH: <i>Drying time and recoat times are temperature, humidity, and film thickness dependent.</i></p> <p>Touch: 20 minutes To Handle: 2 hours</p> <p>Vehicle Type: Alkyd</p> <p>Finish: Flat</p> <p>VOC: 66 g/L</p> <p>Volume Solids: 15 - 22% Weight Solids: 25 - 37% Flash Point: -20°F</p>	PERFORMANCE TESTING
APPLICATION		<p>Technical data furnished herein is accurate and true to the best of our knowledge. However, no guarantee of accuracy is expressed or implied. We assume no responsibility or liability as a result of purchase, coverage, application or injuries resulting in misuse.</p>