



**SHERWIN
WILLIAMS**

102.312

FASTCOAT
Interior / Exterior 100% Acrylic High Gloss
Extra White **A85WV5051**

FASTCOAT Interior / Exterior 100% Acrylic Latex High Gloss is an acrylic latex formulation designed to provide excellent coverage and application to meet the requirements of the professional on both new construction and repaint applications. This product is intended for use on wood, drywall, hardboard, siding, stucco, as well as on doors and trim. **FASTCOAT Interior / Exterior 100% Acrylic Latex High Gloss** offers excellent color retention, mildew, and alkali resistance.

CHARACTERISTICS

Color:	Most Colors	
Finish:	70+ units @ 60°	
Coverage:	350-400 sq. ft./gal. 4.0 mils wet; 1.5 mils dry	
Drying Time: @ 77°F, 50% RH	To touch To recoat	1 hour 2 hours
Flash Point:	N/A	
Tinting with Blend-A-Color:		
Base	oz/gal	Strength
White	0-2	not controlled
A85WV5051		
Volume Solids:	37 ± 2%	
Weight Solids:	49 ± 2%	
Weight Per Gallon:	10.3 lb	
VOC: (less exempt solvents)	203 g/L; 1.69 lb/gal	

APPLICATION

Brush:	No reduction necessary Use a quality nylon/polyester brush
Roller:	No reduction necessary Use a 3/8" to 1/2" nap woven cover
Airless Spray:	
Reduction:	Not Recommended
Pressure:	2000 psi
Tip:	.017 to .021

SURFACE PREPARATION

WARNING! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.

Remove all surface contamination by washing with an appropriate cleaner, rinse thoroughly and allow to dry. Scrape and sand peeled or checked paint to a sound surface. Sand glossy surfaces dull. Seal stains from water, smoke, ink, pencil, grease, etc. with the appropriate primer/sealer.

Masonry, Concrete, Cement, Block, Stucco

All new surfaces must cure according to the supplier's recommendations — usually about 30 days. Remove all form release and curing agents. Rough surfaces can be filled to provide a smooth surface. If painting cannot wait 30 days, allow the surface to cure 7 days and prime the surface with Loxon Concrete & Masonry Primer. Cracks, voids, and other holes should be repaired with an elastomeric patch or sealant.

Primer Loxon Concrete & Masonry Primer

Filler PrepRite Interior/Exterior Latex Block Filler

Wood, Plywood, Composition Board

Sand any exposed wood to a fresh surface. Patch all holes and imperfections with a wood filler or putty and sand smooth. All patched areas must be primed.

Plywood Primer 102 Interior/Exterior Acrylic Primer

Wood Primer 101 Interior/Exterior Alkyd Wood Primer



**SHERWIN
WILLIAMS.**

FASTCOAT

Interior / Exterior 100% Acrylic High Gloss

A85WV5051 Extra White

SURFACE PREPARATION

Mildew

Remove mildew before painting by washing with a solution of 1 part liquid bleach and 3 parts water. Apply the solution and scrub the mildewed area. Allow the solution to remain on the surface for 10 minutes. Rinse thoroughly with water and allow the surface to dry before painting. Wear protective eyewear, waterproof gloves, and protective clothing. Quickly wash off any of the mixture that comes in contact with your skin. Do not add detergents or ammonia to the bleach/water solution.

Caulking

Gaps between windows, doors, trim, and other through-wall openings should be filled with the appropriate caulk after priming the surface.

CLEANUP INFORMATION

Clean spills, spatters, hands and tools immediately after use with soap and warm water. After cleaning, flush spray equipment with mineral spirits to prevent rusting of the equipment. Follow manufacturer's safety recommendations when using mineral spirits.

CAUTIONS

For interior and exterior use

Protect from freezing.

Do not apply at temperature below 50° F.

Non-Photochemically reactive.

See label for additional cautions.

HOTW 08/31/2011 A85WV5051 21 00

PRODUCTS

Color	Rex	SMIS	Size
Extra White	A85WV5051	601143381	Gallons
Extra White	A85WV5051	601143399	Fives

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of The Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Sherwin-Williams representative to obtain the most recent Product Data Sheet.