

# ProMar® 200 Zero V.O.C.

## Interior Latex Eg-Shel

### B20-Series


**SHERWIN  
WILLIAMS.**

#### CHARACTERISTICS

**ProMar® 200 Zero V.O.C. Interior Latex Eg-Shel** is a durable, professional quality, interior vinyl acrylic finish for use on walls, ceilings, and trim of primed plaster, wallboard, wood, masonry, and primed metal.

**Color:** Most Colors  
To optimize hide and color development, always use the recommended P-Shade primer.

**Coverage:** 350-400 sq. ft. per gallon  
@ 4 mils wet  
1.7 mils dry

**Drying Time, @ 77° F, 50% RH:**  
Touch: 1 Hour  
Recoat: 4 Hours  
Drying and recoat times are temperature, humidity, and film thickness dependent.

**Finish:** 15-20 units @ 85°  
5+ units @ 60°

#### **Tinting with CCE:**

Base:	oz. per gallon:	Strength:
High Ref White	0-6	SherColor
Extra White	0-7	SherColor
Deep Base	4-12	SherColor
Ultradeep Base	10-12	SherColor
Real Red	0-12	SherColor
Bright Yellow	0-12	SherColor
Dover White		<b>Do Not Tint</b>

#### **Extra White B20W12651**

(may vary by color)

#### **V.O.C. (less exempt solvents):**

Less than 50 grams per litre; 0.42 lbs. per gallon  
As per 40 CFR 59.406

**Volume Solids:** 42 ±2%

**Weight Solids:** 54 ±2%

**Weight per Gallon:** 10.81 lbs

**Flash Point:** N.A.

**Vehicle Type:** Vinyl Acrylic

**Shelf Life:** 36 months, unopened

**WVP Perms (US):** 54.19 grains/(hr ft<sup>2</sup> in Hg)

#### **Anti-microbial**

This product contains agents which inhibit the growth of mold and mildew on the surface of this paint film.

#### COMPLIANCE

As of 03/03/2025, Complies with:

OTC	Yes
OTC Phase II	Yes
S.C.A.Q.M.D.	Yes
CARB	Yes
CARB SCM 2007	Yes
CARB SCM 2020	Yes
Canada	Yes
LEED® v4 & v4.1 Emissions	Yes
LEED® v4 & v4.1 V.O.C.	Yes
EPD-NSF® Certified	Yes
MIR-Manufacturer Inventory	Yes
MPI®	#52, 52 X-Green®

#### APPLICATION

Apply at temperatures above 50°F  
No reduction needed.

#### **Brush:**

Use a nylon-polyester brush such as Purdy® Clearcut®.

#### **Roller:**

Use a 3/8 to 3/4 inch nap synthetic cover such as Purdy® White Dove™.

For specific brushes and rollers, please refer to our Brush and Roller Guide on [Sherwin-williams.com](http://Sherwin-williams.com)

#### **Spray - Airless:**

Pressure 2000 p.s.i.  
Tip .017-.021 inch

#### APPLICATION TIPS

Make sure product is completely agitated (mechanically or manually) before use.

Priming and application of two coats at the recommended film thickness can help where hiding of a previous coating or application to new drywall is a factor.

Using the same method of application and batch to touch up with as that originally used will help improve touch up.

When original application was by spray, preconditioning of touch up paint by running it through the spray tip will help touch up appearance.

#### SPECIFICATIONS

##### **Block:**

1 coat ConFlex Block Filler\*  
2 coats ProMar 200 Zero V.O.C. Interior Latex

##### **Drywall:**

1 coat ProMar 200 Zero V.O.C. Latex Primer  
2 coats ProMar 200 Zero V.O.C. Interior Latex

##### **Masonry:**

1 coat Loxon Concrete & Masonry Primer\*  
2 coats ProMar 200 Zero V.O.C. Interior Latex

##### **Plaster:**

1 coat Loxon Concrete & Masonry Primer\*  
2 coats ProMar 200 Zero V.O.C. Interior Latex

##### **Wood:**

1 coat Premium Wall & Wood Primer\*  
2 coats ProMar 200 Zero V.O.C. Interior Latex

\*These primers contain less than 50 grams per litre V.O.C.

Other primers may be appropriate.

When repainting involves a drastic color change, a coat of primer will improve the hiding performance of the topcoat color.

# ProMar<sup>®</sup> 200 Zero V.O.C. Interior Latex Eg-Shel

## SURFACE PREPARATION

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a **NIOSH**-approved respirator to control lead exposure. Clean up carefully with a **HEPA** vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at **1-800-424-LEAD** or log on to **www.epa.gov/lead**.

Remove all surface contamination by washing with an appropriate cleaner, rinse thoroughly and allow to dry. Existing peeled or checked paint should be scraped and sanded to a sound surface. Glossy surfaces should be sanded dull. Stains from water, smoke, ink, pencil, grease, etc. should be sealed with the appropriate primer-sealer. Recognize that any surface preparation short of total removal of the old coating may compromise the service length of the system.

### **Caulking:**

Gaps between walls, ceiling, crown moldings, and other interior trim can be filled with the appropriate caulk after priming the surface.

### **Drywall:**

Fill cracks and holes with patching paste-spackle and sand smooth. Joint compounds must be cured and sanded smooth. Remove all sanding dust.

### **Masonry, Concrete, Cement, Block:**

All new surfaces must be cured according to the supplier's recommendations – usually about 30 days. Remove all form release and curing agents. Rough surfaces can be filled to provide a smooth surface. If painting cannot wait 30 days, allow the surface to cure 7 days and prime the surface with Loxon Concrete & Masonry Primer.

## SURFACE PREPARATION

### **Mildew:**

Clean mildew from the Surface: Mildew is a fungus that looks like dirt but won't wash off. Mildew must be removed before painting, or it will grow through any new coat of paint. To remove mildew or suspected mildew, scrub surface before painting with a commercial mildew remover following manufacturer's safety instructions.

### **Plaster:**

Bare plaster must be cured and hard. Textured, soft, porous, or powdery plaster should be treated with a solution of 1 pint household vinegar to 1 gallon of clean water. Repeat until the surface is hard, rinse with clear water and allow to dry.

### **Wood:**

Sand any exposed wood to a fresh surface. Patch all holes and imperfections with a wood filler or putty and sand smooth.

## CAUTIONS

For interior use only.  
Protect from freezing.  
Non-Photochemically reactive.

Before using, carefully read **CAUTIONS on label**.

Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (**NIOSH** approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage.

**FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. **WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.**

HOTW 03/03/2025 B20W12651 34 0  
FRC, SP

## CLEANUP INFORMATION

Clean spills, spatters, hands and tools immediately after use with soap and warm clean water. After cleaning, flush spray equipment with compliant cleanup solvent to prevent rusting of the equipment. Follow manufacturer's safety recommendations when using solvents.