101.16A

ProClassic®
Waterborne Interior Acrylic Satin

B20W01151 Extra White, B20W01153 Deep Base

CHARACTERISTICS

ProClassic® Waterborne Interior Acrylic is a high-quality coating that provides a durable, non-yellowing finish. The excellent flow and leveling characteristics result in a smooth, rich finish equal to an alkyd enamel coating.

Project Uses :
Trim areas and Molding
Cabinets, Doors, Windows
Kitchens, Baths, Locker rooms
Laundry rooms
High Traffic areas

Use On :
Drywall-Plaster
Paneling – Wood
Metal
Concrete-Masonry

Color: Most Colors
To optimize hide and color development, always use the recommended P-Shade primer.

Coverage: 350-400 sq. ft. per gallon @ 4 mils wet, 1.2 mils dry

Drying Time, @ 77°F, 50% RH :
Touch: 1 Hour
Recoat: 4 Hours
Drying and recoat times are temperature, humidity, and film thickness dependent.

Finish: 10-20 units @ 60°

Tinting with CCE only :

Base :	oz. per gallon :	Strength :
Extra White	0-7	SherColor
Deep Base	4-14	SherColor

Extra White B20W01151
(may vary by color)

V.O.C.(less exempt solvents):
less than 50 grams per litre; 0.42 lbs. per gallon
As per 40 CFR 59.406

Volume Solids: 30 ±2%
Weight Solids: 45 ±2%
Weight per Gallon: 10.52 lbs
Flash Point: N.A.
Vehicle Type: Styrene Acrylic
Shelf Life: 36 months, unopened

COMPLIANCE

As of 06/04/2026, Complies with :

OTC	Yes
OTC Phase II	Yes
S.C.A.Q.M.D.	Yes
CARB	Yes
CARB SCM 2007	Yes
CARB SCM 2020	Yes
Canada	Yes
LEED® v4 & v4.1 Emissions	No
LEED® v4 & v4.1 V.O.C.	Yes
EPD-NSF® Certified	No
MIR-Manufacturer Inventory	No
MPI®	No

APPLICATION

Apply at temperatures above 50°F.
No reduction needed.

Brush :
Use a nylon-polyester brush such as Purdy® Nylox™.

Roller :
For best final appearance when rolling, finish off in one direction, especially for dark colors.

Use a high-quality 1/4- 3/4 inch nap synthetic roller cover such as Purdy® White Dove™.

For specific brushes and rollers, please refer to our Brush and Roller Guide.

Spray – Airless :
Pressure 2000 p.s.i.
Tip .015-.021 inch
.011 inch for fine finishing

APPLICATION TIPS

Make sure product is completely agitated (mechanically or manually) before use.

Priming and application of two coats at the recommended film thickness can help where hiding of a previous coating or application to new drywall is a factor.

SPECIFICATIONS

Drywall :
1 coat Premium Wall & Wood Primer
2 coats ProClassic Waterborne Interior

Masonry – Block : (can be filled to provide a smooth surface or primed if it a high pH substrate)
1 coat Loxon Acrylic Block Surfacer
or
1 coat Loxon Concrete & Masonry Primer
2 coats ProClassic Waterborne Interior

Metal – Steel, Aluminum, Galvanized :
1 coat All Surface Enamel Latex Primer
2 coats ProClassic Waterborne Interior

Plaster :
1 coat Loxon Concrete & Masonry Primer
2 coats ProClassic Waterborne Interior

Wood :
1 coat Premium Wall & Wood Primer
2 coats ProClassic Waterborne Interior

If the wood has bleeding (such as tannin or knot-holes), prime with ProBlock Premium All-Purpose Water Based Primer.

Other primers may be appropriate.

When repainting involves a drastic color change, or coating over heavily stained areas, a coat of primer will improve the hiding performance of the topcoat color.

continued on back

ProClassic®

Waterborne Interior Acrylic Satin

SURFACE PREPARATION

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a **NIOSH**-approved respirator to control lead exposure. Clean up carefully with a **HEPA** vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Remove all surface contamination by washing with an appropriate cleaner, rinse thoroughly and allow to dry. Existing peeled or checked paint should be scraped and sanded to a sound surface. Glossy surfaces should be sanded dull. Stains from water, smoke, ink, pencil, grease, etc. should be sealed with the appropriate primer-sealer. Recognize that any surface preparation short of total removal of the old coating may compromise the service length of the system.

Caulking :
Gaps between walls, ceilings, crown moldings, and other interior trim can be filled with the appropriate caulk after priming the surface.

Drywall :
Fill cracks and holes with patching paste-spackle and sand smooth. Joint compounds must be cured and sanded smooth. Remove all sanding dust.

Masonry, Concrete, Cement, Block :
All new surfaces must be cured according to the supplier's recommendations – usually about 30 days. Remove all form release and curing agents. Rough surfaces can be filled to provide a smooth surface. If painting cannot wait 30 days, allow the surface to cure 7 days and prime the surface with Loxon Concrete & Masonry Primer.

SURFACE PREPARATION

Mildew :
Clean mildew from the Surface: Mildew is a fungus that looks like dirt but won't wash off. Mildew must be removed before painting, or it will grow through any new coat of paint. To remove mildew or suspected mildew, scrub surface before painting with a commercial mildew remover following manufacturer's safety instructions.

Plaster :
Bare plaster must be cured and hard. Textured, soft, porous, or powdery plaster should be treated with a solution of 1 pint household vinegar to 1 gallon of clean water. Repeat until the surface is hard, rinse with clean water and allow to dry.

Wood :
Sand any exposed wood to a fresh surface. Patch all holes and imperfections with a wood filler or putty and sand smooth.

CAUTIONS

For interior use only.
Protect from freezing.
Non-Photochemically reactive.

Before using, carefully read **CAUTIONS on label**.

CRYSTALLINE SILICA Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (**NIOSH** approved) or leave the area. Adequate ventilation required when sanding or abrading the dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (**NIOSH** approved). Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. **FIRST AID**: In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. **DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE.** Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long term exposure. **WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.**

HOTW 06/04/2026 B20W01151 40 32 FRC,SP

CLEANUP INFORMATION

Clean spills, spatters, hands and tools immediately after use with soap and warm clean water. After cleaning, flush spray equipment with compliant cleanup solvent to prevent rusting of the equipment. Follow manufacturer's safety recommendations when using solvents. Do not pour unused contents down the drain. Consult with local authorities for method of disposal and recycling.

DANGER: Rags, steel wool, other waste soaked with this product, and sanding residue may spontaneously catch fire if improperly discarded. Immediately place rags, steel wool, other waste soaked with this product, and sanding residue in a sealed, water-filled, metal container. Dispose of in accordance with local fire regulations.

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of The Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Sherwin-Williams representative or visit www.paintdocs.com to obtain the most current version of the PDS and/or an SDS