



**SHERWIN  
WILLIAMS.**

# SHER-WOOD® 7311W Wiping Stain Base

Wiping Stain Base.....S64N70009

<b><u>DESCRIPTION</u></b>	<b><u>CHARACTERISTICS</u></b>	<b><u>SPECIFICATIONS</u></b>
<p><b>SHER-WOOD® 7311W Wiping Stain base</b> is a ready to use wipe stain base for achieving excellent grain definition on interior wood products. Dark colors can be achieved with outstanding clarity and excellent adhesion. They are developed to give good grain definition. Designed to be used with Hostafine (H) series, 896's or Kem Aqua Colorants to a maximum total level of 20 % by weight.</p> <p><b>Air Quality Data:</b></p> <ul style="list-style-type: none"> <li>• Non-photochemically reactive</li> <li>• Volatile Organic Compounds (VOC) theoretical as packaged, maximum less exempt solvents: 5.48 lb/gal, 656 g/L.</li> </ul> <p>Volatile Hazardous Air Pollutants (VHAPS) as packaged maximum: less than 0.8 lbs per pound of solids</p> <p>VOC compliance limits vary from state to state; please consult local Air Quality rules and regulations</p> <p>An Environmental Data Sheet is available from your local Sherwin-Williams facility, or at <a href="http://www.paintdocs.com">www.paintdocs.com</a>.</p>	<p><b>Volume Solids:</b> 2 ± 1%</p> <p><b>Weight Solids:</b> 3 ± 1%</p> <p><b>Viscosity:</b> 58-82 seconds #2 Zahn Cup</p> <p><b>Drying (77°F, 50% RH):</b> To Seal Coat: 30-45 minutes</p> <p><b>Flash Point:</b> N/A</p> <p><b>Package Life:</b> 1 year, unopened</p>	<p><b>Surface preparation:</b> <b>Wood - New Work (interior only):</b> Must be clean, dry, and finish sanded. Substrate should be free of grease, oil, dirt, fingerprints, and any contamination to ensure optimum adhesion and coating performance properties. Moisture content of wood should be 6 to 8%.</p> <p><b>Previously finished wood (interior only):</b> Strip old finishes completely and remove all contaminants from the surface. Make sure surface is dry. Finish as new work.</p> <p><b>Testing:</b> The information, data, and recommendations set forth in this Product Data Sheet are based upon test results believed to be reliable. However, due to the wide variety of substrates, substrate properties, surface preparation methods, equipment and tools, application methods, and environments, the customer should test the complete system for adhesion, compatability and performance prior to full scale application.</p>

<b><u>APPLICATION</u></b>	<b><u>ADDITIONAL INFORMATION</u></b>	<b><u>CAUTIONS</u></b>
<p data-bbox="272 149 412 170">Typical Setups</p> <p data-bbox="120 222 237 243"><b>Reduction:</b></p> <p data-bbox="120 275 493 296">Reduce with Deionized Water if needed</p> <p data-bbox="120 373 217 394"><b>Cleanup:</b></p> <p data-bbox="120 401 565 449">Clean tools/equipment immediately after use with reduction solvent</p> <p data-bbox="120 478 553 527">Follow manufacturer's safety Recommendations when using any solvent.</p>	<ul data-bbox="586 201 1040 470" style="list-style-type: none"> <li>• Like most water based products, Sher-Wood 5211W pigmented Primer should not be force dried with high speed air for the first few minutes to avoid mud cracking</li> <li>• Can be topcoated with a variety of Sherwin Williams water based and solvent borne clear coats.</li> <li>• Can be tinted with up to 20% by weight with Chroma-Chem 896, Hostafine H pigments or Kem Aqua Colorants</li> </ul> <p data-bbox="586 520 976 569">All trademarks are the property of their respective owners.</p>	<p data-bbox="1065 201 1503 222"><b>FOR INDUSTRIAL SHOP APPLICATION ONLY</b></p> <p data-bbox="1057 254 1520 323"><b>Thoroughly review product label and Safety Data Sheet (SDS) for safety information and cautions prior to using this product.</b></p> <p data-bbox="1057 352 1520 470">To obtain the most current version of the Environmental Data Sheet (EDS), Product Data Sheet (PDS), or Safety Data Sheet (SDS) please visit your local Sherwin-Williams facility or <a href="http://www.paintdocs.com">www.paintdocs.com</a>.</p> <p data-bbox="1057 499 1520 548">Please direct any questions or comments to your local Sherwin-Williams facility.</p> <p data-bbox="1057 894 1520 1037"><b>Note:</b> All purchases of products from Sherwin-Williams are exclusively subject to Sherwin-Williams' terms and conditions of sale which can be found <a href="#">by following this link (click here)</a>. Please review these terms and conditions prior to the purchase of the products.</p> <p data-bbox="1057 1066 1520 1457">Sherwin-Williams warrants the product to be free of manufacturing defect in accordance with Sherwin-Williams' quality control procedures. Except for the preceding sentence, due to factors that are outside of Sherwin-Williams' control, including substrate selection, and customer handling, preparation, and application, Sherwin-Williams cannot make any other warranties related to the product or the performance of the product. <b>SHERWIN-WILLIAMS DISCLAIMS ALL WARRANTIES OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTY OF MERCHANTABILITY, THE IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE.</b></p> <p data-bbox="1057 1486 1520 1717">Liability for products proven to be defectively manufactured will be limited solely to replacement of the defective product or the refund of the purchase price paid for the defective product, as determined by Sherwin-Williams. Under no circumstances shall Sherwin-Williams be liable for indirect, special, incidental or consequential damages, lost profits or punitive damages arising from any cause whatsoever.</p>