



SHERWIN-WILLIAMS® Synthetic Shellac Primer Aerosol Primer

SW Sales Number: 650863053

Manufacturer Product Number: C47000000

PRODUCT DESCRIPTION	APPLICATION	CAUTIONS
<p>Synthetic Shellac Primer provides the performance of a true shellac, blocking the most resistant odors and stains including smoke and fire damage, pet odors, water stains, tannins and wood knots. Seals porous substrates and provides an excellent foundation for a flawless finish.</p>	<p>Use outdoors or in well-ventilated area. Protect surrounding areas from overspray. Shake can for 2 minutes after ball within begins to rattle. Repeat 10 seconds after each minute of use. Test spray in an inconspicuous area for compatibility. Hold can 8"-12" from surface, spray in a sweeping motion from side to side with slight overlap. Avoid runs and drips by applying multiple thin coats. After priming stained areas, wait 1 hour and test for bleed-through by applying top-coat over small area. After use, to prevent clogs, hold can upside down and spray until clear gas appears. To clean paint on tip, wear eye protection, and wipe off with mineral spirits-DO NOT stick pin in tip opening. Clean overspray with mineral spirits, following solvent manufacturer's instructions. Recycle empty can and cap per local regulations.</p>	<p>CONTAINS CRTSTALLINE SILICA, KETONES, TOLUENE AND XYLENE. DANGER! EXTREMELY FLAMMABLE. Keep away from heat, sparks and open flame. Vapors will accumulate readily and may ignite explosively. Keep area ventilated during use and until all vapors are gone. DO NOT SMOKE - Extinguish all flames, pilot lights and heaters - Turn off stoves, electric tools and appliances, and any other sources of ignition. CONTENTS UNDER PRESSURE. Avoid prolonged exposure to sunlight or heat from radiators, stoves, hot water and other heat sources that may cause bur- sting. Do not puncture, incinerate burn or store above 120°F. Keep upright in a cool, dry place. Do not discard empty can in trash compactor. VAPOR HARMFUL. Use with adequate ventilation. Avoid continuous breathing of vapor and spray mist. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection (NIOSH approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. FIRST AID: In case of eye contact, flush thoroughly with large amounts of water for 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water. In case of respiratory difficulty, provide fresh air and call physician.</p>
PAINTING CONDITIONS		
<p>Use outdoors or in a well-ventilated area. Best results when air and surface temperature is 40°F(4.4°C)-80°F(26.7°C) and humidity is below 85%.</p>	CHARACTERISTICS	
	<p>Color: White</p> <p>Coverage: Up to 25 square feet</p> <p>Drying Time: 40°F(4.4°C)-80°F(26.7°C) and humidity is below 85%</p> <p><i>Drying time and recoat times are temperature, humidity, and film thickness dependent.</i></p> <p>Touch: 1 hour</p> <p>Recoat: Wait 5 minutes between initial coats; dries in 1 hour; wait 3 hours before applying top coat.</p>	<p>DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long term exposure. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.</p>
SURFACE PREPARATION		PERFORMANCE TESTING
<p>WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Hotline at 1-800-424-LEAD or log onto www.epa.gov/lead. Surfaces should be clean, dull and dry.</p>	<p>Vehicle Type: Acrylic Copolymer</p> <p>Finish: Ultra-Flat</p> <p>Volume Solids: 18%</p> <p>Weight Solids: 41%</p>	<p>Technical data furnished herein is accurate and true to the best of our knowledge. However, no guarantee of accuracy is expressed or implied. We assume no responsibility or liability as a result of purchase, coverage, application or injuries resulting in misuse.</p>