

# Solo®

## Interior-Exterior Satin

### A73-Series



**SHERWIN  
WILLIAMS®**

#### CHARACTERISTICS

**Solo Satin Interior-Exterior** waterbased paint creates a scrubbable finish that is resistant to burnishing, wearing, and blocking. **Solo Satin** combines a lower luster appearance with ease of application and is designed for doors, trim, walls, and shutters.

**Color:** Most Colors  
To optimize hide and color development, always use the recommended P-Shade primer.

**Coverage:** 350-400 sq. ft. per gallon  
@ 4 mils wet  
1.6 mils dry

#### **Drying Time, @ 77° F, 50% RH:**

Touch: 1 Hour  
Recoat: 5 Hours  
Drying and recoat times are temperature, humidity, and film thickness dependent.

**Finish:** 20-30 units @ 60°

#### **Tinting with CCE only:**

Base:	oz. per gallon:	Strength:
Extra White	0-4	SherColor
Deep Base	4-12	SherColor
Ultra Deep	4-12	SherColor

#### **Extra White A73W00051**

(may vary by color)

#### **V.O.C. (less exempt solvents):**

Less than 50 grams per litre; 0.42 lbs. per gallon  
As per 40 CFR 59.406

**Volume Solids:** 40 ±2%

**Weight Solids:** 52 ±2%

**Weight per Gallon:** 10.41 lbs (4.72 kg)

**Flash Point:** N.A.

**Vehicle Type:** Styrenated Acrylic

**Shelf Life:** 36 months, unopened

**WVP Perms (US):**  
30.06 grains/(hr ft<sup>2</sup> in Hg)

#### COMPLIANCE

As of 05/09/2025, Complies with:

OTC	Yes
OTC Phase II	Yes
S.C.A.Q.M.D.	Yes
CARB	Yes
CARB SCM 2007	Yes
CARB SCM 2020	Yes
Canada	Yes
LEED® v4 & v4.1 Emissions	Yes
LEED® v4 & v4.1 V.O.C.	Yes
EPD-NSF® Certified	Yes
MIR-Manufacturer Inventory	Yes
MPI®	No

#### APPLICATION

Apply at temperatures above 50°F (10°C).  
No reduction needed.

#### **Brush:**

Use a nylon-polyester brush such as Purdy® Clearcut® Elite™.

#### **Roller:**

Use a 3/8 to 3/4 inch nap synthetic cover such as Purdy® Marathon®.

For specific brushes and rollers, please refer to our Brush and Roller Guide on [Sherwin-Williams.com](http://Sherwin-Williams.com)

#### **Spray - Airless:**

Pressure 2000 p.s.i.  
Tip .013-.015 inch

#### APPLICATION TIPS

Make sure product is completely agitated (mechanically or manually) before use.

#### SPECIFICATIONS

Apply 2 topcoats of Solo Satin directly over existing properly prepared, interior or exterior coatings. New interior bare drywall, cured plaster and masonry (cured with a pH of less than 10), and non-bleeding wood, prime with appropriate primer.

#### **Interior**

##### **Drywall:**

1 coat ProMar 200 Zero V.O.C. Latex Primer  
2 coats Solo Satin

##### **Plaster:**

1 coat Loxon Concrete & Masonry Primer  
2 coats Solo Satin

##### **Wood:**

1 coat Premium Wall & Wood Primer  
2 coats Solo Satin

##### **Interior and Exterior**

##### **Aluminum, Galvanized & Steel: (if needed)**

1 coat All Surface Enamel Latex Primer  
2 coats Solo Satin

##### **Block:**

1 coat ConFlex Block Filler  
2 coats Solo Satin

##### **Masonry, Cement, Stucco:**

1 coat Loxon Concrete & Masonry Primer  
2 coats Solo Satin

##### **Exterior**

##### **Wood, Composition Board:**

1 coat Exterior Oil-Based Wood Primer  
or  
1 coat Exterior Latex Wood Primer  
2 coats Solo Satin

Other primers may be appropriate.

When repainting involves a drastic color change, a coat of primer will improve the hiding performance of the topcoat color.

Application on exterior surfaces should be limited to trim, doors, and shutters. This product is not ideal for whole house painting.

Solo®

# Interior-Exterior Satin

## SURFACE PREPARATION

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a **NIOSH**-approved respirator to control lead exposure. Clean up carefully with a **HEPA** vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

Remove all surface contamination by washing with an appropriate cleaner, rinse thoroughly and allow to dry. Existing peeled or checked paint should be scraped and sanded to a sound surface. Glossy surfaces should be sanded dull. Stains from water, smoke, ink, pencil, grease, etc. should be sealed with the appropriate primer-sealer. Recognize that any surface preparation short of total removal of the old coating may compromise the service length of the system.

### **Aluminum and Galvanized Steel:**

Wash to remove any oil, grease, or other surface contamination. All corrosion must be removed with sandpaper, wire brush, or other abrading method. Prime with All Surface Latex Primer.

### **Caulking:**

Gaps between walls, ceiling, crown moldings, and other interior trim can be filled with the appropriate caulk after priming the surface.

### **Concrete Block:**

All new surfaces must be cured according to recommendations—usually about 30 days. Rough surfaces can be filled with ConFlex Block Filler to provide a smooth surface. The filler must be thoroughly dry before topcoating.

### **Drywall:**

Fill cracks and holes with patching paste-spackle and sand smooth. Joint compounds must be cured and sanded smooth. Remove all sanding dust.

### **Masonry, Concrete, Cement, Block:**

All new surfaces must be cured according to the supplier's recommendations – usually about 30 days. Remove all form release and curing agents. Rough surfaces can be filled to provide a smooth surface. If painting cannot wait 30 days, allow the surface to cure 7 days and prime the surface with Loxon Concrete & Masonry Primer.

### **Stucco:**

Remove any loose stucco, efflorescence, or laitance. Allow new stucco to cure at least 30 days before painting. If painting cannot wait 30 days, allow the surface to dry 7 days and prime with Loxon Concrete & Masonry Primer. Repair cracks, voids, and other holes with an elastomeric patch or sealant.

## SURFACE PREPARATION

### **Mildew:**

Clean mildew from the Surface: Mildew is a fungus that looks like dirt but won't wash off. Mildew must be removed before painting, or it will grow through any new coat of paint. To remove mildew or suspected mildew, scrub surface before painting with a commercial mildew remover following manufacturer's safety instructions.

### **Steel:**

Rust and mill scale must be removed using sandpaper, wire brush, or other abrading method. Bare steel must be primed the same day as cleaned. Prime with All Surface Latex Primer.

### **Plaster:**

Must be cured, usually 30 days, and hard. If painting cannot wait, allow the surface to dry 7 days and prime with Loxon Concrete and Masonry Primer. Soft, porous, or powdery plaster should be treated with a solution of 1 pint household vinegar to 1 gallon of water. Repeat until the surface is hard, rinse with water and allow to dry before painting.

### **Wood, Plywood, Composition Board:**

Clean the surface thoroughly then sand any exposed wood to a fresh surface. Patch all holes and imperfections with a wood filler or putty and sand smooth. All patched areas must be primed. Knots and some woods, such as redwood and cedar, contain a high amount of tannin, a colored wood extract. If applied to these bare woods, it may show some staining.

**Exterior:** If staining persists, spot prime severe areas with 1 coat of Exterior Oil-Based Wood Primer prior to using.

**Interior:** If staining persists, spot prime severe areas with 1 coat of Multi-Purpose Oil-Based Primer.

## CAUTIONS

Protect from freezing.  
Non-Photochemically reactive.

Before using, carefully read **CAUTIONS on label**.

**CRYSTALLINE SILICA** Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (**NIOSH** approved) or leave the area. Adequate ventilation required when sanding or abrading the dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (**NIOSH** approved). Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. **FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. **DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE.** Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long term exposure. **WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.**

**HOTW 05/09/2025 A73W00051 17 36 SP, FRC**

## CLEANUP INFORMATION

Clean spills, spatters, hands and tools immediately after use with soap and warm clean water. After cleaning, flush spray equipment with compliant cleanup solvent to prevent rusting of the equipment. Follow manufacturer's safety recommendations when using solvents.