

# ConFlex® UltraCrete™ Acrylic Texture Coating

CF17W0801 Fine Extra White, CF17W0811 Medium Extra White  
CF17W0821 Extra Coarse Extra White



**SHERWIN  
WILLIAMS.**

## 5CHARACTERISTICS

**ConFlex® UltraCrete™ Acrylic Textured Coating** is an 100% acrylic aggregate-filled coating used to produce a textured finish on properly prepared interior or exterior surfaces.

The pleasing texture that results has the ability to minimize defects and irregularities found on poured cement aggregate block and sheetrock joints. The excellent adhesion of the product makes this suitable for side walls, as well as for ceilings.

May be used on concrete, aggregate block, sheetrock, cement, primed steel, and primed wood.

Suitable for use on overhead horizontal surfaces providing the adjoining parapet top caps, balconies, soffits, floors, roofs, and decks are sealed against water penetration.

**Finish:** Low Eg-Shel

**Color:** Many Colors

**Coverage:**  
Textured 50-80 sq. ft. per gallon  
per coat  
Coverage will vary with the substrate and the texture.

### **Drying Schedule 77°F @ 50% RH:**

**To touch** 30 minutes to 1 hour

**To recoat** 2 hours

Drying and recoat times are temperature, humidity, and film thickness dependent.

### **Tinting with CCE:**

Base	oz. per gallon	Strength
Extra White	0-6	SherColor

### **Extra White CF17W0801**

(may vary by product)

### **V.O.C. (less exempt solvents):**

less than 50 grams per litre; 0.42 lbs. per gallon  
As per 40 CFR 59.406

<b>Volume Solids:</b>	41 ±2%
<b>Weight Solids:</b>	54 ±2%
<b>Weight per Gallon:</b>	10.49 lbs
<b>Flash Point:</b>	N.A.
<b>Vehicle Type:</b>	100% Acrylic
<b>Shelf Life:</b>	36 months, unopened

### **Mildew Resistant**

This coating contains agents which inhibit the growth of mildew on the surface of this coating film.

## COMPLIANCE

As of 8/20/2025, Complies with:

<b>OTC</b>	Yes
<b>OTC Phase II</b>	Yes
<b>S.C.A.Q.M.D.</b>	Yes
<b>CARB</b>	Yes
<b>CARB SCM 2007</b>	Yes
<b>CARB SCM 2020</b>	Yes
<b>Canada</b>	Yes
<b>LEED® v4 &amp; v4.1 Emissions</b>	No
<b>LEED® v4 &amp; v4.1 V.O.C.</b>	Yes
<b>EPD-NSF® Certified</b>	No
<b>MIR-Manufacturer Inventory</b>	No
<b>MPI®</b>	#41, 42

## APPLICATION

**Temperature:** air, surface, and material  
minimum 40°F

**Reduction:** **Do not reduce**  
**Brush and Roller:** small areas only

Apply at temperatures above 40°F. When the air temperature is at 40°F, substrates may be colder; prior to painting, check to be sure the air, surface, and material temperature are above 40°F and at least 5°F above the dew point.

Do not apply at air or surface temperatures below 40°F or when air or surface temperatures may drop below 40°F within 48 hours.

### FINE AND MEDIUM TEXTURES:

**Spray Unit:** Graco TexSpray RTX 5000 pi  
**Pressure:** 30-35 p.s.i. air at the pump  
**Tip:** 3/16-1/4 inch  
**Reduction:** None

### EXTRA COARSE TEXTURE:

**Spray Unit:** Graco 10:1 President Texture Pump

**Spray:** Unit must be specifically designed for aggregate coatings.

## RECOMMENDED SYSTEMS

**Concrete, CMU, Stucco, Masonry, Cement Composition:**

**ConFlex UltraCrete** can be used without a primer on properly prepared surfaces with a pH between 6 and 9. On high pH surfaces, 9 or greater, prime with:

1 coat Loxon Concrete & Masonry Primer

Or

1 coat Loxon Acrylic Block Surfacer

1-2 coats of ConFlex UltraCrete

### **Tilt-Up, Precast:**

**ConFlex UltraCrete** can be used without a primer on properly prepared surfaces with a pH between 6 and 9 (when applied at recommended coverage rates).

1 coat of ConFlex UltraCrete

### **Steel:**

1 coat All Surface Enamel Primer

1-2 coats of ConFlex UltraCrete

### **Wood, (Exterior) Composition Board:**

1 coat Exterior Oil-Based Wood Primer

1-2 coats of ConFlex UltraCrete

### **Drywall (Interior):**

1 coat ProMar 200 Zero VOC Latex Primer

1-2 coats of ConFlex UltraCrete

### **Drywall (exterior):**

1 coat Exterior Latex Wood Primer

1-2 coats of ConFlex UltraCrete

# ConFlex® UltraCrete™ Acrylic Texture Coating

## SURFACE PREPARATION

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

Remove all surface contamination by washing with an appropriate cleaner, rinse thoroughly and allow to dry. Existing peeled or checked paint should be scraped and sanded to a sound surface. Glossy surfaces should be sanded dull. Stains from water, smoke, ink, pencil, grease, etc. should be sealed with the appropriate primer-sealer. Recognize that any surface preparation short of total removal of the old coating may compromise the service length of the system.

### **Masonry, Concrete, CMU, Stucco:**

Remove all dirt, dust, mildew, loose particles, laitance, foreign material, peeling and defective coatings, chalk, form release agents, moisture curing membranes, etc. All new surfaces must be cured according to the supplier's recommendations—usually about 30 days. If painting cannot wait 30 days, allow the surface to cure 7 days at 75°F and prime the surface with Loxon Concrete & Masonry Primer or Loxon Acrylic Block Surfacers to fill Block, and CMU.

On tilt-up and poured-in-place concrete, commercial detergents and sandblasting may be necessary to remove sealers, release compounds, and to provide an anchor pattern. Allow the surface to dry thoroughly. Concrete and mortar must be cured at least 30 days and a pH of less than 9 to apply this product directly. Fill bugholes, air pockets, cracks, and other voids with an acrylic elastomeric patch or sealant. Rough surfaces can be filled to provide a smooth surface.

### **Cement Composition Siding-Panels:**

Remove all dirt, dust, grease, oil, loose particles, laitance, foreign material, and peeling or defective coatings. Allow the surface to dry thoroughly. If the surface is new, test it for pH, if the pH is higher than 9, prime with Loxon Concrete and Masonry Primer.

### **Caulking:**

Gaps between windows, doors, trim, and other through-wall openings can be filled with the appropriate caulk after priming the surface.

### **Wood:**

Sand any exposed wood to a fresh surface. Patch all holes and imperfections with a wood filler or putty and sand smooth. Bare wood and all patched areas must be primed.

## SURFACE PREPARATION

### **Mildew:**

Clean mildew from the Surface: Mildew is a fungus that looks like dirt but won't wash off. Mildew must be removed before painting, or it will grow through any new coat of paint. To remove mildew or suspected mildew, scrub surface before painting with a commercial mildew remover following manufacturer's safety instructions.

## PHYSICAL PROPERTIES

**CF17W0801**  
(may vary by product)

### **Wind Driven Rain<sup>1</sup>:**

Method: ASTM D6904-03  
Result: Pass

### **Water Vapor Permeance<sup>2</sup>:**

Method: Based on ASTM D1653  
14 day cure @77°F & 50% RH  
Result: 23.00 perms

### **Flexibility:**

Method: ASTM D522  
method B, 180° bend, 1/4 inch mandrel  
Result: Pass

### **Alkali Resistance:**

Method: ASTM D1308  
Result: Pass

### **Impact Resistance:**

Method: ASTM D2794  
Result: Pass

### **Salt Spray<sup>3</sup>:**

Method: ASTM B117  
300 hours Blasted Steel panels  
Result: no blisters, 0 rust Creep, rating of 10

### **Adhesion:**

Method: ASTM D3359  
Method B, smooth concrete  
Result: Pass

<sup>1</sup> 1 coat Loxon Masonry Primer at 3.2 mils D.F.T.  
2 coats ConFlex UltraCrete at 13.5-18 mils D.F.T.

<sup>2</sup> 1coat ConFlex UltraCrete at 9.4 mils D.F.T.

<sup>3</sup> 1 coat Pro Industrial Pro-Cryl Primer  
1 coat ConFlex UltraCrete

## CAUTIONS

Protect from freezing.

Not for use on top side horizontal surfaces (floors, roofs, decks, etc.) where water will collect.

Not for use below grade or underwater. Will not withstand hydrostatic pressure.

On areas subject to wear, some of the texture may be abraded off.

Not for use in areas subject to vehicle traffic.

Before using, carefully read **CAUTIONS** on label.

**CRYSTALLINE SILICA:** Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (**NIOSH** approved) or leave the area. Adequate ventilation required when sanding or abrading the dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (**NIOSH** approved). Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. **FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. **DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE.** Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long term exposure. **WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.**

HOTW 08/20/2025 CF17W0801 39 48  
FRC,SP

## CLEANUP INFORMATION

Clean spills, splatters, hands and tools immediately after use with soap and warm clean water. After cleaning, flush spray equipment with compliant cleanup solvent to prevent rusting of the equipment. Follow manufacturer's safety recommendations when using solvents.