

SuperDeck® Stain & Sealer Remover

651044562 (US), 651045304 (Canada)


**SHERWIN
WILLIAMS®**

CHARACTERISTICS

SuperDeck® Stain & Sealer Remover is specifically designed to help remove semi-transparent and weathered solid latex and oil-based stains from decks and other exterior wood. **SuperDeck Stain & Sealer Remover** allows you to change the color of your deck or siding by restoring the natural beauty of the wood.

Where to use:

SuperDeck Stain & Sealer Remover can be used on many exterior wood surfaces such as decks, siding and fences and will remove the following stains and finishes:

- Polyurethane and some weathered latex paint
- Oil-based toners, transparent, semi-transparent, and weathered solid stains
- Water-based toners, transparent, semi-transparent, and weathered stains
- Water-reducible toners, transparent, semi-transparent and weathered solid stains
- Old, weathered, clear protective finishes

SuperDeck Stain & Sealer Remover will help restore color to severely weathered and discolored wood. Test product on an inconspicuous area before applying to your entire deck. Do not use on new, untreated wood or new wood treated with a clear protective finish. **SuperDeck Stain & Sealer Remover** may darken the appearance of new wood.

Coverage: 150 sq. ft. per gallon
Depending upon the condition and porosity of the wood.

Appearance: Clear, amber liquid

pH: 13.5

Solvent: Water

Size: 1 gallon

651044562

V.O.C. (less exempt solvents):

less than 50 grams per litre; 0.42 lbs. per gallon
As per 40 CFR 59.406

Volume Solids: 6.4 ± 2%

Weight Solids: 13.8 ± 2%

Weight per Gallon: 9.02 lbs

Flash Point: N.A.

Type: Sodium Hydroxide

COMPLIANCE

As of 06/16/2020, Complies with:

OTC	Yes
OTC Phase II	Yes
SCAQMD	Yes
CARB	Yes
CARB SCM 2007	Yes
Canada	Yes
LEED® v4 & v4.1 Emissions	No
LEED® v4 & v4.1 VOC	Yes
EPD-NSF® Certified	No
MIR-Manufacturer Inventory	No
MPI®	No

APPLICATION

Before using, carefully read **CAUTIONS** on label.

Add contents of container to plastic bucket.

DO NOT MIX WITH ANY OTHER PRODUCT.

Do not use metal containers. Apply **SuperDeck Stain & Sealer Remover** liberally with brush or roller. Clean small areas one at a time allowing product to sit for 10-15 minutes. Scrub the surface with a synthetic stiff bristle brush (do not use a wire or natural bristle brush) to remove those finishes that do not come up immediately. Do not allow **SuperDeck Stain & Sealer Remover** to dry during application. If stubborn areas remain, repeat the application in those areas.

Be cautious with wet surfaces as they may be slippery.

Thoroughly rinse the surface with fresh water from a hose, removing all residue. Any residue left on the surface may interfere with the drying or adhesion of topcoats.

Rinse surrounding area and vegetation with water.

SuperDeck Stain & Sealer Remover may darken Western Red Cedar and Redwood.

SuperDeck Revive™ must be used after **SuperDeck Stain & Sealer Remover** to neutralize the surface and as a second step to bring back the natural color of the wood.

Note: If the grain of your wood raises after application, sand the surface lightly.

APPLICATION TIPS

Read all the package directions before using. It is always recommended to test any cleaner on a small, inconspicuous area prior to use.

Thoroughly read and understand all the label cautions prior to using any cleaner.

Be sure that the cleaner is appropriate for the dirt-contamination.

Do not mix together any cleaning compounds containing bleach and ammonia.

Abrasive cleansers may damage a paint film, use very carefully.

Bleach and bleaching type cleaners may damage or discolor existing paint films. Bleach alternative cleaning solutions would be advised.

Revive™

Stain & Sealer Remover

SURFACE PREPARATION

WARNING! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at **1-800-424-LEAD** (in US) or contact your local health authority.

Be sure the surface is free of any loose dirt and debris. If the surface is extremely dry or in direct, hot sunlight, dampen with water. Thoroughly wet plants and shrubs and cover to protect them from overspray. Uncover promptly after cleaning. Remove all deck furniture and decorative items. Do not allow **SuperDeck Stain & Sealer Remover** to come into contact with finished or aluminum surfaces. Rinse immediately after use on metal to avoid pitting or discoloration. Do not allow **SuperDeck Stain & Sealer Remover** to come into prolonged contact with clothing, carpet, or fabric, as damage may occur.

Plan the application; for horizontal surfaces, work backwards so that you do not walk on the surface being treated. For vertical surfaces, work from the top down. Treat small areas one at a time.

Using the right cleaner often makes the cleaning easier. Prior to using **SuperDeck Stain & Sealer Remover**, some general cleaning may be needed. Clean all surfaces completely with the appropriate cleaner based on the conditions. Rinse the surface completely and allow the surface to dry thoroughly.

SuperDeck® Deck Wash

- Mildew stain, Algae stain
- Weathered wood (bleaches wood)
- Gray wood (bleaches wood)

SuperDeck® Revive™

- Tannin Bleed, Nail stain
- Weathered wood (restores color)
- Gray wood (restores color), Mill Glaze

SuperDeck® Stain & Sealer Remover

- Weathered, gray wood
- Old Paint & Stain

SURFACE PREPARATION

Carefully follow all label instructions. Thoroughly rinse the surface to remove all residue and allow to thoroughly dry before coating.

- Read all the package directions before using. It is always recommended to test any cleaner on a small, inconspicuous area prior to use.
- Do not apply over sealed surfaces.
- To determine if the surface is sealed, test the absorbency by sprinkling water on it. If the water penetrates quickly, the surface is ready to finish. If the water beads up or does not penetrate, remove the coating-sealer and allow to dry. Test for absorbency again.
- **Failure to follow application and surface preparation guidelines may result in premature coating failure.**

Mildew: Prior to attempting to remove mildew, it is always recommended to test any cleaner on a small, inconspicuous area prior to use. Bleach and bleaching type cleaners may damage or discolor existing paint films. Bleach alternative cleaning solutions may be advised.

Mildew may be removed before painting by washing with a solution of 1 part liquid bleach and 3 parts water. Apply the solution and scrub the mildewed area. Allow the solution to remain on the surface for 10 minutes. Rinse thoroughly with water and allow the surface to dry before painting. Wear protective eyewear, waterproof gloves, and protective clothing. Quickly wash off any of the mixture that comes in contact with your skin. Do not add detergents or ammonia to the bleach-water solution.

CAUTIONS

This product must be applied outdoors to wood intended for exterior use only.

Not for interior use.

Storage: Protect from freezing. Do not store below 30°F.

Before using, carefully read **CAUTIONS on label**

DANGER! CAUSES EYE, SKIN AND RESPIRATORY TRACT BURNS. Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. **FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water for 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water. In case of respiratory difficulty, provide fresh air and call physician. If swallowed, do not induce vomiting. Call Poison Control Center, hospital emergency room, or physician immediately. **WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.**

HOTW 06/16/2020 651044562 01 00
FRC,SP

CLEANUP INFORMATION

Rinse equipment and brushes with soap and water immediately after use.