

Builders Solution™**Interior Latex Matte**

A64WQ0051 Extra White

**SHERWIN
WILLIAMS.****CHARACTERISTICS**

Builders Solution™ Interior Latex Matte is a high-quality product designed for the professional. This product has good washability and durability as well as excellent touch-up. With AccuTouch™ Technology for Excellent Touch-Up.

Builders Solution Interior Latex is recommended for interior application on walls and ceilings of primed plaster, wallboard, wood, masonry, and primed metal.

Color: Many Colors
To optimize hide and color development, always use the recommended P-Shade primer.

Coverage: 350-400 sq. ft. per gallon
@ 4 mils wet 1.3 mils dry

Drying Time, @ 77° F, 50% RH:

Touch: 1 Hour
Recoat: 4 Hours

Drying and recoat times are temperature, humidity, and film thickness dependent.

Finish: 1-3 units @ 85°
0-5 units @ 60°

Tinting with CCE only:

Base: oz. per gallon **Strength:**
Extra White 0-6 SherColor

Extra White A64W00051

(may vary by color)

V.O.C. (less exempt solvents):

Less than 50 grams per litre; 0.42 lbs. per gallon
As per 40 CFR 59.406

Volume Solids: 33 ±2%

Weight Solids: 52 ±2%

Weight per Gallon: 11.46 lbs

Flash Point: N.A.

Vehicle Type: Vinyl Acrylic

Shelf Life: 36 months, unopened

WVP Perms (US): 55.39 grains/(hr ft² in Hg)

COMPLIANCE

As of 11/10/2022, Complies with :

OTC	Yes
OTC Phase II	Yes
S.C.A.Q.M.D.	Yes
CARB	Yes
CARB SCM 2007	Yes
CARB SCM 2020	Yes
Canada	Yes
LEED® v4 & v4.1 Emissions	No
LEED® v4 & v4.1 V.O.C.	Yes
EPD-NSF® Certified	No
MIR-Manufacturer Inventory	No
MPI®	No

APPLICATION

Apply at temperatures above 50°F
No reduction needed.

Brush:

Use a nylon-polyester brush.

Roller:

Use a 3/8-3/4 inch nap synthetic cover.

Spray - Airless:

Pressure 2000 p.s.i.
Tip .017-.021 inch

APPLICATION TIPS

Make sure product is completely agitated (mechanically or manually) before use.

Priming and application of two coats at the recommended film thickness can help where hiding of a previous coating or application to new drywall is a factor.

Using the same method of application and batch to touch-up with as that originally used will help improve touch-up.

When original application was by spray, preconditioning of touch-up paint by running it through the spray tip used will help touch up appearance.

SPECIFICATIONS**Block:**

1 coat ConFlex Block Filler
2 coats Builders Solution Interior Latex

Drywall:

Self-prime using 2 coats Builders Solution Interior Latex
or
1 coat ProMar 200 Zero V.O.C. Primer
or
1 coat Builders Solution Primer-Surfacer
2 coats Builders Solution Interior Latex

Masonry:

1 coat Loxon Concrete and Masonry Primer
2 coats Builders Solution Interior Latex

Plaster:

1 coat Loxon Concrete and Masonry Primer
2 coats Builders Solution Interior Latex

Wood, Composition Board:

1 coat Premium Wall and Wood Primer
2 coats Builders Solution Interior Latex
If the wood has bleeding (such as tannin or knot-holes), prime with Multi-Purpose Primer.

Other primers may be appropriate.

When re-painting involves a drastic color change, a coat of primer will improve the hiding performance of the topcoat color.

Builders Solution™

Interior Latex Matte

SURFACE PREPARATION

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a **HEPA** vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting your local health authority.

Remove all surface contamination by washing with an appropriate cleaner, rinse thoroughly and allow to dry. Existing peeled or checked paint should be scraped and sanded to a sound surface. Glossy surfaces should be sanded dull. Stains from water, smoke, ink, pencil, grease, etc. should be sealed with the appropriate primer-sealer. Recognize that any surface preparation short of total removal of the old coating may compromise the service length of the system.

Caulking:

Gaps between walls, ceiling, crown moldings, and other interior trim can be filled with the appropriate caulk after priming the surface.

Drywall:

Fill cracks and nail holes with patching paste-spackle and sand smooth. Joint compounds must be cured and sanded smooth. Remove all sanding dust.

Masonry, Concrete, Cement, Block:

All new surfaces must be cured according to the supplier's recommendations – usually about 30 days. Remove all form release and curing agents. Rough surfaces can be filled to provide a smooth surface. If painting can not wait 30 days, allow the surface to cure 7 days and prime the surface with Loxon Concrete & Masonry Primer.

Plaster:

Bare plaster must be cured and hard. Textured, soft, porous, or powdery plaster should be treated with a solution of 1 pint household vinegar to 1 gallon of water. Repeat until the surface is hard, rinse with clear water and allow to dry.

Wood:

Sand any exposed wood to a fresh surface. Patch all holes and imperfections with a wood filler or putty and sand smooth.

SURFACE PREPARATION

Mildew:

Prior to attempting to remove mildew, it is always recommended to test any cleaner on a small, inconspicuous area prior to use. Bleach and bleaching type cleaners may damage or discolor existing paint films. Bleach alternative cleaning solutions may be advised.

Mildew may be removed before painting by washing with a solution of 1 part liquid bleach and 3 parts clean water. Apply the solution and scrub the mildewed area. Allow the solution to remain on the surface for 10 minutes. Rinse thoroughly with clean water and allow the surface to dry before painting. Wear protective eyewear, waterproof gloves, and protective clothing. Quickly wash off any of the mixture that comes in contact with your skin. Do not add detergents or ammonia to the bleach-water solution.

CAUTIONS

For interior use only.
Protect from freezing.
Non-Photochemically reactive.

Before using, carefully read **CAUTIONS on label**.

MAY IRRITATE EYES. Do not get in eyes. Keep out of reach of children. **FIRST AID TREATMENT.** Contains: surfactants. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 15 minutes.

HOTW 11/10/2022 A64WQ0051 29 37
FRC

CLEANUP INFORMATION

Clean spills, spatters, hands and tools immediately after use with soap and warm water. After cleaning, flush spray equipment with compliant cleanup solvent to prevent rusting of the equipment. Follow manufacturer's safety recommendations when using solvents.