

# WoodScapes®

## Premium Translucent Finish

A15C00204/A15CQ0204 Satin Natural


**SHERWIN  
WILLIAMS.**

### CHARACTERISTICS

**WoodScapes Premium Translucent Finish Satin Natural** is a high-quality choice for protecting exterior wood siding, log and timber framed homes, doors and trim, fencing, rails, and other vertical wood surfaces.

This high solids exterior wood finish provides excellent water repellency and is resistant to UV fading.

This product contains agents which inhibit the growth of mildew on the surface of this paint film.

Use on:

- Unfinished Pine
- Cedar and Redwood
- Fir
- Most Softwoods

**Color:** Natural & 8 Tintable\* Wood Colors

#### **Coverage:**

Smooth Surfaces 400-500 sq. ft. per gallon  
Rough Sawn 250-350 sq. ft. per gallon  
Depending on porosity and texture.

**Note:** New wood normally requires less product than old, weathered wood. This is due to older wood being more porous than newer wood.

#### **Drying Time, @ 77° F, 50% RH:**

Touch: 8-12 Hours  
Recoat: 24 Hours

Drying and recoat times are temperature, humidity, and film thickness dependent.

**Finish:** Satin 25-30 units @ 60°

#### **Tinting: Tint with BAC**

<b>Base</b>	<b>oz. per gallon</b>	<b>SherColor</b>
Natural Base	0-6	Yes*

#### **Satin Natural A15C00204**

(may vary by color)

#### **V.O.C. (less exempt solvents):**

less than 275 grams per litre; 2.29 lbs. per gallon  
As per 40 CFR 59.406

**Volume Solids:** 47 ±2%

**Weight Solids:** 47 ±2%

**Weight per Gallon:** 8.99 lbs

**Flash Point:** 111 F° PMCC

**Vehicle Type:** Alkyd

**Shelf Life:** 36 months, unopened

### COMPLIANCE

As of 05/27/2025, Complies with:

OTC	Yes
OTC Phase II	Yes
S.C.A.Q.M.D.	Yes
CARB	Yes
CARB SCM 2007	Yes
CARB SCM 2020	Yes
Canada	Yes
LEED® v4 & v4.1 Emissions	N/A
LEED® v4 & v4.1 V.O.C.	Yes
EPD-NSF® Certified	N/A
MIR-Manufacturer Inventory	N/A
MPI®	No

### APPLICATION

For best results, apply in shade with surface temperatures between 40°F and 95°F. Do not apply if temperatures will fall below 40°F or if rain is expected within 24 hours after application. Do not apply over wet or damp surfaces.

#### **Do not reduce.**

**Brush:** Use a natural bristle brush such as Sherwin-Williams Deck & Siding Brush.

**Roller:** Use a high-quality woven roller cover such as Purdy® White Dove™.

For specific brushes and rollers, please refer to our Brush and Roller Guide on [sherwin-williams.com](http://sherwin-williams.com).

#### **Spray - Airless:**

Pressure	1500 - 2000 p.s.i.
Tip	.011-.017 inch

### APPLICATION TIPS

Thoroughly stir contents before and occasionally during use. For uniformity, mix all cans together before use. Do not mix with any other stains or coatings. A sample brush out is recommended to ensure desired color and appearance satisfaction.

All surfaces must be clean, dry and free from dirt, mildew stains, dust and other foreign matter. Remove surface stains, dirt and failed oxidized stains or finishes.

Different wood species, textures and natural color will affect the finished shade.

### APPLICATION TIPS

Apply without thinning by brush, roller or spray. If sprayed, use the lowest possible pressure needed for a reasonable spray pattern. Also, when spraying be sure to back brush-roll to work the product smoothly and evenly into the wood. This will decrease the possibility of pools or puddles on the surface and ensure a properly penetrated finish.

Penetration will vary depending on porosity of the surface. Thoroughly coat cut ends and joints. Keep the leading edge wet and distribute the finish evenly. Use natural breaks as boundaries to divide large areas into smaller, more manageable ones.

### SPECIFICATIONS

#### **Wood:**

2 coats WoodScapes Premium Translucent Finish

Two coats are recommended for maximum protection and full coverage. Allow 24 hours dry time between coats.

#### **\*Color Palette available in SherColor**

SW 3601 Butternut  
SW 3602 Cedar  
SW 3603 Dark Oak  
SW 3604 Mahogany  
SW 3605 Natural  
SW 3606 Natural Oak  
SW 3607 Teak  
SW 3608 Mission Brown

## Premium Translucent Finish

### SURFACE PREPARATION

**Warning!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting: US - National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead); Canada - your local health authority

Remove all existing paint and replace any deteriorated substrate. Although this can be applied over earlier translucent finishes, some of the old color may be visible through this translucent finish. Recognize that any surface preparation short of total removal of the old coating may compromise the service length of the system.

Remove all surface contamination by washing with an appropriate cleaner, especially in areas not exposed to direct weathering such as under eaves and porch ceilings. Rinse thoroughly and allow the surface to dry. Test the absorbency of the wood by sprinkling water on the surface. If the water penetrates into the wood quickly, the wood is ready to finish. If the water beads up or does not penetrate, remove the existing finish or contaminant. Then test for absorbency again. Do not apply coating over wet or damp surfaces.

#### **Caulking:**

Apply appropriate caulking and patching material to cracks, nail holes or tother surface imperfections. Filled areas will take the finish differently than bare wood. Consider using a caulk that is a color similar to the stain color.

#### **Mill Glaze:**

Mill glaze is a glossy finish on new, smooth sawn wood or on the peaks of some textured wood. This must be removed by sanding to allow the finish to penetrate.

#### **Cedar & Redwood:**

Follow cleaning or stripping with Superdeck® Revive™ Deck & Siding Brightener to remove tannin stains and brighten wood to its original color.

### SURFACE PREPARATION

#### **Mildew:**

Clean mildew from the Surface: Mildew is a fungus that looks like dirt but won't wash off. Mildew must be removed before painting, or it will grow through any new coat of paint. To remove mildew or suspected mildew, scrub surface before painting with a commercial mildew remover following manufacturer's safety instructions.

#### **Pressure Treated Wood:**

Test the absorbency of the wood by sprinkling water on the surface. If the water penetrates into the wood quickly, the wood is ready to finish. If the water beads up or does not penetrate, remove existing finish or contaminant. Then test for absorbency again. Prepare the surface like any other wood surface.

Due to the green tone of many brands of pressure treated lumber, the color of the finished wood may look different from that of the desired look. Check the color on a test area prior to finishing the entire project.

#### **Smooth or Rough Wood Siding and Plywood:**

Sand any exposed wood to a fresh surface. Replace any deteriorated wood.

### CAUTIONS

Maintenance clean by using a non-chlorinated bleach alternative.

For exterior use on exterior wood only.

Do not use on roofs.

Not for use on horizontal surfaces, such as a roof, or floor, where water may collect.

**DANGER! HARMFUL OR FATAL IF SWALLOWED. COMBUSTIBLE! VAPOR HARMFUL. IRRITATES EYES, SKIN AND RESPIRATORY TRACT.**

Before using, carefully read **CAUTIONS** on label.

Contains **ALIPHATIC HYDROCARBONS** and **AROMATIC HYDROCARBONS**. Contents are **COMBUSTIBLE**. Keep away from heat and open flame. **VAPOR HARMFUL**. Use only with adequate ventilation. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. **FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water for 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water. In case of respiratory difficulty, provide fresh air and call physician. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. **DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE.** Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. **WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.**

HOTW 05/27/2025 A15C00204 12 273  
FRC,SP

### CLEANUP INFORMATION

Clean spills, spatters, hands, and tools immediately after use with compliant cleanup solvent. Follow manufacturer's safety recommendations when using solvents.

**DANGER:** Rags, steel wool, other waste soaked with this product, and sanding residue may spontaneously catch fire if improperly discarded. Immediately place rags, steel wool, other waste soaked with the product, and sanding residue in a sealed, water-filled, metal container. Dispose of in accordance with local fire regulations.