


**SHERWIN
WILLIAMS.**

Painters Edge Plus™ (Formerly Painters Edge)

Interior Latex Eg-Shel

PE4600051 Extra White

CHARACTERISTICS

Painters Edge Plus™ Interior Latex Eg-Shel dries to a durable, professional finish, making it ideal for use by contractors and builders on properly prepared drywall, plaster, masonry and incidental wood surfaces.

Color: Many Colors

To optimize hide and color development, always use the recommended P-shade primer.

Coverage: 350-400 sq. ft. per gallon
@ 4 mils wet 1.4 mils dry

Drying Time, @ 77° F, 50% RH:

Touch: 1 Hour
Recoat: 4 Hours

Drying and recoat times are temperature, humidity, and film thickness dependent.

Finish: 15-20 units @ 85°

Tinting with CCE only:

| | | |
|--------------|-----------------------|------------------|
| Base: | oz. per gallon | Strength: |
| Extra White | 0-5 | SherColor |

Extra White PE4600051

(may vary by color)

V.O.C. (less exempt solvents):

Less than 50 grams per litre; 0.42 lbs. per gallon
As per 40 CFR 59.406

Volume Solids: 34 ±2%

Weight Solids: 47 ±2%

Weight per Gallon: 10.52 lbs

Flash Point: N.A.

Vehicle Type: Vinyl Acrylic

Shelf Life: 36 months, unopened

WVP Perms (US): 89.13 grains/(hr ft² in Hg)

COMPLIANCE

As of 11/01/2022, Complies with :

| | |
|----------------------------|-----|
| OTC | Yes |
| OTC Phase II | Yes |
| S.C.A.Q.M.D. | Yes |
| CARB | Yes |
| CARB SCM 2007 | Yes |
| CARB SCM 2020 | Yes |
| Canada | Yes |
| LEED® v4 & v4.1 Emissions | No |
| LEED® v4 & v4.1 V.O.C. | Yes |
| EPD-NSF® Certified | No |
| MIR-Manufacturer Inventory | No |
| MPI® | No |

APPLICATION

Apply at temperatures above 50°F
No reduction needed.

Brush:

Use a nylon-polyester brush.

Roller:

Use a 3/8-3/4 inch nap synthetic cover.

Spray - Airless:

| | |
|----------|----------------|
| Pressure | 2000 p.s.i. |
| Tip | .017-.021 inch |

APPLICATION TIPS

Make sure product is completely agitated (mechanically or manually) before use.

Priming and application of two coats at the recommended film thickness can help where hiding of a previous coating or application to new drywall is a factor.

Using the same method of application and batch to touch-up with as that originally used will help improve touch-up.

When original application was by spray, preconditioning of touch-up paint by running it through the spray tip used will help touch up appearance.

SPECIFICATIONS

Block:

1 coat ConFlex Block Filler
2 coats Painters Edge Plus Interior Latex

Drywall:

1 coat ProMar 200 Zero V.O.C. Primer
2 coats Painters Edge Plus Interior Latex

Masonry:

1 coat Loxon Concrete and Masonry Primer
2 coats Painters Edge Plus Interior Latex

Plaster:

1 coat Loxon Concrete and Masonry Primer
2 coats Painters Edge Plus Interior Latex

Wood, Composition Board:

1 coat Premium Wall and Wood Primer
2 coats Painters Edge Plus Interior Latex

If the wood has bleeding (such as tannin or knot-holes), prime with Multi-Purpose Primer.

Other primers may be appropriate.

When re-painting involves a drastic color change, a coat of primer will improve the hiding performance of the topcoat color.

Painters Edge Plus™ (Formerly Painters Edge)

Interior Latex Eg-Shel

SURFACE PREPARATION

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Remove all surface contamination by washing with an appropriate cleaner, rinse thoroughly and allow to dry. Existing peeled or checked paint should be scraped and sanded to a sound surface. Glossy surfaces should be sanded dull. Stains from water, smoke, ink, pencil, grease, etc. should be sealed with the appropriate primer-sealer. Recognize that any surface preparation short of total removal of the old coating may compromise the service length of the system.

Caulking:

Gaps between walls, ceiling, crown moldings, and other interior trim can be filled with the appropriate caulk after priming the surface.

Drywall:

Fill cracks and nail holes with patching paste-spackle and sand smooth. Joint compounds must be cured and sanded smooth. Remove all sanding dust.

Masonry, Concrete, Cement, Block:

All new surfaces must be cured according to the supplier's recommendations – usually about 30 days. Remove all form release and curing agents. Rough surfaces can be filled to provide a smooth surface. If painting can not wait 30 days, allow the surface to cure 7 days and prime the surface with Loxon Concrete & Masonry Primer.

Plaster:

Bare plaster must be cured and hard. Textured, soft, porous, or powdery plaster should be treated with a solution of 1 pint household vinegar to 1 gallon of water. Repeat until the surface is hard, rinse with clear water and allow to dry.

Wood:

Sand any exposed wood to a fresh surface. Patch all holes and imperfections with a wood filler or putty and sand smooth.

SURFACE PREPARATION

Mildew:

Prior to attempting to remove mildew, it is always recommended to test any cleaner on a small, inconspicuous area prior to use. Bleach and bleaching type cleaners may damage or discolor existing paint films. Bleach alternative cleaning solutions may be advised.

Mildew may be removed before painting by washing with a solution of 1 part liquid bleach and 3 parts clean water. Apply the solution and scrub the mildewed area. Allow the solution to remain on the surface for 10 minutes. Rinse thoroughly with clean water and allow the surface to dry before painting. Wear protective eyewear, waterproof gloves, and protective clothing. Quickly wash off any of the mixture that comes in contact with your skin. Do not add detergents or ammonia to the bleach-water solution.

CAUTIONS

For interior use only.
Protect from freezing.
Non-Photochemically reactive.

Before using, carefully read **CAUTIONS on label**.

CRYSTALLINE SILICA: Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Adequate ventilation required when sanding or abrading the dried film. If adequate ventilation cannot be provided, wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. **FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, Call Poison Control Center, hospital emergency room, or physician immediately. **DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE.** Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long term exposure. **WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.**

HOTW 11/01/2022 PE4600051 27 00
FRC,SP

CLEANUP INFORMATION

Clean spills, spatters, hands and tools immediately after use with soap and warm water. After cleaning, flush spray equipment with compliant cleanup solvent to prevent rusting of the equipment. Follow manufacturer's safety recommendations when using solvents.